MX-B456W

A compact office MFP that offers high productivity and smart workflows for a busy office.



- A4 Black and White MFP with speeds of 45ppm
- Advanced system/data protection and access control including firmware and self-recovery and whitelisting
- Easy UI mode on 7-0inch colour LCD touchscreen with control panel that tilts at various angles for easy access
- Easy access to public cloud services such as Dropbox via single sign-
- Built in wireless connectivity enables easy access from mobile devices and flexible placement
- 100-sheet Duplex Single Pass Feeder scans documents at up to 110 ipm*1
- NFC*2 and QR code enable easy direct connection between MFP and mobile device
- Supports Sharpdesk Mobile print/scan application and various mobile printing services
- Accommodates 2 Ethernet networks*3
- Space-efficient inner finisher (option) automates document sorting and stapling
- Standard paper tray and multi bypass tray accommodate a wide variety of paper sizes, including A6
- Business Card feeder on the DSPF*4 scans batches of up to 25 cards



^{*1:} Originals per minute; when feeding A4 (8 1/2" x 11") sheets. *2: The NFC interface is for Android™ devices. Requires commercially available NFC card reader. *3: Requires commercially available Ethernet adaptor that supports two lines. *4: This function is enabled via Qualcomm® DirectOffice™ technology.

Specifications

Engine speed B/W ppm (A4) 45 Paper size: Min.-Max A6 – A4 Paper weight (g/m2) 60 - 220 Paper capacity:Std (sheets) 550 Paper capacity: Max. (sheets) 2350 Warm Up Time (sec.) 20 Memory general min/max (GB) Harddisk STD Harddisk capacity (GB) 500 Duplex STD 220 - 240V, 50 / 60Hz

Power requirements - rated local AC voltage

Power consumption (kW) 1.84 Dimensions (mm) 492 x 517 x 638

Weight (Kg) 33

DOCUMENT FEEDER

Original capacity (sheets) 100

DOCUMENT FILING

Document filing (Standard / Option) STD Document filing capacity- main and custom 20000 folders (pages) 10000

Document filing capacity- quick file folder

(pages) Stored iobs Copy, print, scan, fax transmission Storage folders Quick file folder, main folder, custom folder (max. 1000)

Confidential storage

Fax (Standard / Option) STD

MH / MR / MMR / JBIG Compression method **Communication protocol** Super G3 / G3

Transmission time (sec)

Modem Speed (bps) 33.600 - 2.400 Transmission resolution

STD 203,2 x 97,8 dpi / Ultra Fine 406.4 x 391 dpi

Document Size (Min) Α5 Document Size (Max) Α4 Memory (MB) 1024

Grev Scale levels 256 Dial Registration; rapid/speed dial 2000 **Broadcast Transmission (max. destinations)** 500

WIRELESS LAN

Compliant regulation IEEE802.11n/g/b

Infrastructure mode, Software AP Access mode

mode

Security

WPA2 EAP

Original paper size (Max.) First copy out time B/W (sec.) 3,7 E-sort Std Continuous copy (Max. copies) 9999 Resolution Scan B/W (dpi) 600 x 600

Resolution Print (dpi) 600 x 600,600 x 400

Gradation (equivalent levels) - B/W 256 25 - 400, (25 - 200 using RSPF / Zoom range (%)

DSPF) in 1% increments Preset copy ratios 10 ratios (5R / 5E)

SCANNER

Network Scanner (Standard / Option) Scan method Push scan and Pull scan Resolution push scan (dpi)

Resolution pull scan (dpi)

9,600 dpi via user setting File formats TIFF, PDF, PDF / A-1a, PDF / A-1b,

encrypted PDF, XPS, compact PDF, JPEG, searchable PDF, OOXML (docx, xlxs, pptx), text (TXT), rich

75,100, 150,200, 300,400, 600,50 to

100,150, 200,300, 400,600

text (RTF) Sharpdesk

STD

Scanner utilities Scan destinations Desktop Scan destination FTP, Email Scan destination Network folder

Scan destination USB memory

PRINTER

Resolution (dpi) Network Printer (Standard / Option)

Interface Std/Opt

Supported OS Standard

Network protocols

Printing protocols

PDL Std/Opt

Available fonts

WFP WPA / WPA2-mixed PSK WPA / WPA2-mixed EAP, WPA2 PSK,

600 x 600,9, 600 (equivalent) x 600 Standard Ethernet and WiFi 802.11

STD USB 2.0,10Base-T / 100Base-TX

/ 1000Base-T / 802.11 b / g / n

Windows Server®

2008,2008R2,2012, 2012R2,2016, 2019, Windows® 7,8.1,10, Mac OS X 10.9, 10.10, 10.11, 10.12, 10.13, 10.14,

10.15

TCP / IP, WEP, WPA / WPA2-mixed PSK, WPA-WPA2- mixed EAP, WPA

PSK, WPA2 EAP

LPR, Raw TCP (port 9100), POP3 (email printing), HTTP, FTP for

downloading print files, IPP, SMB,

Standard: PCL 6 emulation. Genuine Adobe® PostScript®3

80 (PCL), 139 (PS3)

FINISHING

Output Capacity Max. 250 Staple Capacity (sheets) Max. Off-set shifting OPT

Design and specifications are subject to change without prior notice. Microsoft, Windows Server, and Windows are either registered trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademark or registered trademark or trademarks or trademark or trademark or trademark or trademark or trademarks or trademarks or trademarks or trademark or trademarks or trademarks or trademark or trademarks or trademarks or trademark or trademarks or tradem

